

TES Reliable in Quality

TES-3910 Trms Clamp Meter (DC/AC 1000A)

- True RMS reading on AC and DC+AC mode
- Inrush current measurement
- Phase Rotation check (3 Φ)
- Variable-frequency drive (VFD) V & Hz measurement
- Lo-Z voltage measurement to drain ghost voltages





Reliable in Quality

TES-3910 Trms Clamp Meter (DC/AC 1000A)

FEATURES

- Variable-frequency drive (VFD) V & Hz measurement
- Lo-Z voltage measurement to drain ghost voltages
- Check 3 ϕ phase sequence
- True RMS reading on AC and DC+AC mode
- Inrush current measurement
- μ A measurement for HVAC flame sensors
- mV measurement range to interface with other accessories
- Crest Factor & Harmonic ratio measurement
- Data hold, Auto hold & Peak hold mode
- Max/Min/Avg record mode
- Data memory & read function

GENERAL SPECIFICATIONS

Max Wire Diameter : 30mm

Category : CAT III 1000V, CAT IV 600V

Accessories : Instruction Manual, Battery, Carrying case & Test Lead

Weight/Size : 236(L)x80(W)x39(T)mm/326g

ELECTRICAL SPECIFICATIONS

ELECTRICAL SPECIFICATIONS (23°C \pm 5°C)

AC Current (40Hz to 400Hz) : Trms

Range	Resolution	Accuracy	Sensitivity	Overload Protection
99.99A	10mA	$\pm 2\% \pm 20$ dgts (40 to 400Hz)	0.10A	1000A
999.9A	100mA		1.0A	

DC Current

Range	Resolution	Accuracy	Sensitivity	Overload Protection
99.99A	10mA	$\pm 2\% \pm 20$ dgts	0.10A	1000A
999.9A	100mA		1.0A	

ACA Inrush Current

Range	Resolution	Sensitivity	Measurement Time	Overload Protection
99.99A	0.01A	>5A	100mS	1000AAC
999.9A	0.1A	>50A		

μ A Trms : (AC+DC) (Burden Voltage : 5mV/ μ A)

Range	Resolution	Accuracy	Sensitivity	Overload Protection
99.99 μ A	10nA	$\pm 1\% \pm 20$ dgts	0.20 μ A	1000V
999.9 μ A	100nA		2.0 μ A	

AC Voltage (50Hz to 400Hz) : Trms

Range	Resolution	Accuracy	Sensitivity	Overload Protection
999.9mV	0.1mV	$\pm 1\% \pm 20$ dgts (50, 60Hz)	2.0mV	1000V
9.999V	1mV		0.020V	
99.99V	10mV	$\pm 2\% \pm 20$ dgts (40 to 400Hz)	0.20V	
999.9V	100mV		2V	

DC Voltage

Range	Resolution	Accuracy	Sensitivity	Overload Protection
999.9mV	0.1mV	$\pm 1.0\% \pm 20$ dgts	2.0mV	1000V
9.999V	1mV		0.020V	
99.99V	10mV		0.20V	
999.9V	100mV		2V	

Resistance (Continuity<40 Ω on the 999.9 Ω range)

Range	Resolution	Accuracy	Overload Protection
999.9 Ω	100m Ω	$\pm 1\% \pm 10$ dgts	1000V
9.999K Ω	1 Ω		
99.99K Ω	10 Ω		
999.9K Ω	100 Ω		

3 ϕ Phase sequence indication

Range	Frequency Response	Overload Protection
80V to 480V	50Hz / 60Hz	1000V

Diode (Continuity<40mV)

Range	Resolution	Accuracy	Overload Protection
3.000V	1mV	$\pm 2\% \pm 1$ dgt	1000V

Frequency

Range	Resolution	Accuracy	Sensitivity
40Hz/1KHz	0.1Hz	$\pm 0.5\%$ rdg ± 2 dgts	ACV>1.2V, ACA>6A



TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei, Taiwan

Tel : (02) 2799-3660 Fax : 886-2-2799-5099

E-mail : tes@ms9.hinet.net <http://www.tes.com.tw>